

O-CE7-XSXXYY-L-E- X 10.000 MHz

Precision Ultra Low Phase Noise OCXO in 36x27 mm “Europack”


Product Data Sheet

Features

- SC-cut crystal
- High Stability
- Low Aging
- Ultra Low Phase Noise
 Extraordinary (E) -87 dBc/Hz at 0.1 Hz
 -120 dBc/Hz at 1 Hz
 -148 dBc/Hz at 10 Hz
 -170 dBc/Hz on the floor
- Sine Wave output +14 dBm TYP

Applications

- Instrumentation
- GPS
- Telecommunication Systems
- Radar
- COTS/Dual use



H code	Height, inches, TYP
5	0.5 (12.7 mm)
6	0.63 (16 mm)
7	0.75 (19 mm)

Code 6 is standard unless code 5 is requested. Code 7 is for special requirements.



Parameter	Symb	Condition	Min	Typ	Max	Unit	Note
Absolute Maximum Ratings							
Input Break Down Voltage	V _{cc}	12 V supply 5 V supply	-0.5 -0.5		13.0 5.5	V	
Storage temper.	T _s		-50		90	°C	
Control Voltage	V _c		-1		11	V	Slope option "L"
Electrical (6)							
Frequency	F			10.000		MHz	
Frequency stability	$\Delta F/F$	vs. Temp.	From ± 2.0			ppb	See chart below
		vs. Supply		0.1	0.2	ppb/5%V _{cc}	
Aging		per day		2E-10			after 30 days
		per year, first year		2E-8			
		second year		1E-8			
		10 years		1E-7			
Allan Deviation		0.1 s		2E-13	3E-13		Static and benign conditions
		1 s		4E-13	5E-13		
		10 s		2E-12	4E-12		
		100 s		5E-12	7E-12		
SSB Phase Noise (achieved after 10 minutes warm-up)		0.1 Hz		-89	-87	dBc/Hz	Static and benign conditions
		1 Hz			-120		
		10 Hz			-148		
		100 Hz			-160		
		1 KHz			-168		
		10 KHz			-170		
		100 KHz			-170		
Retrace		After 30 minutes			± 2	ppb	24 Hours off 1*
G-sensitivity		Gamma 3 directions			± 1.0	ppb/G	
Input Voltage	V _{cc}		4.75	5.0	5.25	V	See chart below to specify
			11.4	12.0	12.6		
Power consumption, Still air	P	steady state, 25°C start-up @ -30°C		1.0	1.4	W	Still air
				2.5	3.2		
Spectral Purity		Subharmonics Spurious		none	-135	dBc	Produced by device, not set-up related
		Harmonics		-35	-30		
Load	AC-coupled 50 Ohm (Sine-wave)						
Warm-up time	τ	to 0.1ppm accuracy		3	5	minutes	
Output Waveform	Sine-wave						
Output Power			+13	+14	+15	dBm	
Control voltage	V _c		0		10.0	V	
Input impedance	Z _{in}	At V _c pin	10			KOhm	
Modulation bandwidth	F _m		DC		1	KHz	
Reference Voltage	V _{ref}			4.5		V	
Output Impedance		At V _{ref} pin		100		Ohm	
Pull range		from nominal F	± 0.3	± 0.4		ppm	
Deviation slope		Monotonic, positive		0.12		ppm/V	
Setability	V _{c0}	@25°C, F _{nom} .		4.5 \pm 0.5		V	
Initial calibration	$\Delta F/F$	V _c = 4.5 V			± 70	ppb	Internally biased 3*, 1*



Notes:

- 1*. Longer storage time, especially at low temperatures, may affect both retrace and setability parameters. It may require few days on power for re-stabilization.
- 2*. All parameters, unless otherwise specified, are guaranteed over specified temperature and Vcc range. The tests of phase noise and short-term stability, however, are performed at room temperature in benign and static environment only.
- 3*. It is highly recommended, if possible, to avoid tuning the calibration externally in order to avoid deteriorating the phase noise and short-term stability performance. If necessary, metal film low noise resistors with bias from Vref port must be used.

Environmental and Mechanical

Operating temp. range	0°C to 70°C Standard, Other options – see chart below
Storage Temperature	-50°C to 90°C
Mechanical Shock	Per MIL-STD-202, 30G, 11ms
Vibration	Per MIL-STD-202, 5G to 2000 Hz
Soldering Conditions	260°C for 10s Max leads only

Electrical Connections

Pin Out	Pin #1-Vc ; Pin#2 – Vref ; Pin #3 – Vcc; Pin #4- Output ; Pin #5- GND;
----------------	--



Creating a Part Number

Q - C E 7 X S XX YY - L - E - X 10.000 MHz

OCXO
Conventional Power Package Code
 E 5 pin 36x27mm

Height code per dwg

Supply Voltage

Code	Specification
0	5V ± 5%
F	12V± 5%

Output

Code	Specification
S	Sinewave

Temperature Stability

Code	Specification
19	±1x10 ⁻⁹
30	±3x10 ⁻¹⁰
20	±2x10 ⁻¹⁰
YZ	+Yx10 ^{-Z}

Environmental

Code	Specification
L	Contains a level of lead that is in excess of RoHS directive and is not designed for reflow
R	RoHS compliant, not designed for reflow

Phase Noise (See Table)

Code	Specification
E	Extraordinary

Deviation slope

Code	Specification
L	Positive, 0 to 10 V

Temperature Range

Code	In 5°C steps
First letter	Lowest temperature from I = -10°C
Second letter	Highest temperature to W = 70°C
Examples	
HR	-5°C to 45°C
GU	-10°C to 60°C
GX	-10°C to 75°C

Not all combinations are available. Consult Factory.

7*Temperature Code Table

Letter	Temp °C	Letter	Temp °C	Letter	Temp °C	Letter	Temp °C	Letter	Temp °C	Letter	Temp °C
A	-40	F	-15	K	10	P	35	U	60	Z	85
B	-35	G	-10	L	15	Q	40	V	65		
C	-30	H	-5	M	20	R	45	W	70		
D	-25	I	0	N	25	S	50	X	75		
E	-20	J	5	O	30	T	55	Y	80		

PRELIMINARY

