



## LVC MOS SJ-A1420 Series

Rev. V

### Description


The **SJ-A1420 Series** of quartz crystal oscillators provide enable/disable 3-state LVC MOS compatible signals for bus connected systems. Supplying Pin 1 of the SJ-A1420 units with a logic "1" or open enables its pin 3 output. In the disabled mode, pin 3 presents a high impedance to the load. All units are designed to survive standard wave soldering operations without damage.

### Features

- Wide frequency range— 1.0MHz to 80.0MHz
- User specified tolerance available
- Space-saving alternative to discrete component oscillators
- High shock resistance, to 3000g
- Metal lid electrically connected to ground to reduce EMI
- 3.3 Volt operation
- COTS/Dual use
- High Reliability - NEL HALT/HASS qualified for crystal oscillator start-up conditions
- Low Jitter - Wavecrest jitter characterization available
- High Q Crystal actively tuned oscillator circuit
- Power supply decoupling internal
- No internal PLL avoids cascading PLL problems
- Low power consumption
- Gold plated leads
- RoHS Compliant, Lead Free Construction

### Electrical Connection

Pin	Connection
1	Enable/Disable Input
2	Ground
3	Output
4	V <sub>DD</sub>



**SJ-A1420 Series** Continued  
LVCMOS

**Rev. V**

## Operating Conditions and Output Characteristics

### Electrical Characteristics

Parameter	Symbol	Conditions	Min	Typical	Max
Frequency	-----	-----	1.0MHz	-----	80.0MHz
Duty Cycle	-----	@ $V_{DD}/2$	45/55%	-----	55/45%
Logic 0	$V_{OL}$	@ 600 $\mu$ A	-----	-----	0.2V
Logic 1	$V_{OH}$	@ 600 $\mu$ A	$V_{DD}-0.2V$	-----	-----
Rise & Fall Time	tr,tf	10-90%	-----	-----	8 ns
Tpz	-----	-----	-----	-----	25 ns
Enable/Disable					
Logic High Voltage	-----	-----	1.6V	-----	-----
Enable/Disable					
Logic Low Voltage	-----	-----	-----	-----	0.4V
Jitter, Integrated	J	Integrated from phase noise, 12kHz to 20MHz, RMS	-----	0.1 ps	-----
Jitter, Wavecrest Characterized <sup>(2)</sup>	-----	Random Period	-----	2.3ps	-----
		Accum, pk-to-pk	-----	26ps	-----
Phase Noise	$\xi(\Delta f)$	@ 10Hz	-----	-70 dBc/Hz	-----
		@ 100Hz	-----	-105 dBc/Hz	-----
		@ 1kHz	-----	-130 dBc/Hz	-----
		@ 10kHz	-----	-145 dBc/Hz	-----
		@ 100kHz	-----	-150 dBc/Hz	-----
		@ >1Mhz	-----	-150 dBc/Hz	-----
Frequency Stability <sup>(1)</sup>	dF/F	Overall conditions including: voltage, calibration, temp., 10 yr aging, shock, vibration	-100ppm	-----	+100ppm

### General Characteristics

Parameter	Symbol	Conditions	Min	Typical	Ma3x
Supply Voltage <sup>(3)</sup>	$V_{DD}$	3.3V $\pm$ 10%	2.97V	3.3V	3.63V
Supply Current	$I_{DD}$	No Load	0.0 mA	25mA	40mA
Output current	$I_O$	-----	0.0 mA	-----	$\pm$ 16.0 mA
Operating temperature	$T_A$	-----	0°C	-----	70°C
Storage temperature	$T_S$	-----	-55°C	-----	125°C
Power Dissipation	$P_D$	-----	-----	-----	145 mW
Load	---	-----	-----	-----	15pf
Start-up time	$t_s$	-----	-----	2 ms	10 ms


### Environmental and Mechanical Characteristics

Mechanical Shock	Per MIL-STD-202, Method 213, Condition E
Thermal Shock	Per MIL-STD-883, Method 1011, Condition A
Vibration	0.060" double amplitude 10 Hz to 55 Hz, 35g's 55Hz to 2000 Hz
Hermetic Seal	Leak rate less than $1 \times 10^{-8}$ atm.cc/sec of helium

#### Footnotes:

- 1) Standard frequency stability ( $\pm$ 20, $\pm$ 25, $\pm$ 50ppm & others available)
- 2) Jitter performance is frequency dependent. Please contact factory for full Wavecrest characterization.
- 3) Internal high frequency power source decoupling.

#### Test Load:



#### Creating a Part Number

**SJ - A142X - FREQ**

#### Package Code

SJ 4 J Lead SMD

#### Tolerance/Performance

0  $\pm$ 100ppm 0-70°C  
 1  $\pm$ 50ppm 0-70°C  
 7  $\pm$ 25ppm 0-70°C  
 9 Customer Specific  
 A  $\pm$ 20ppm 0-70°C  
 B  $\pm$ 50ppm -40 to +85°C  
 C  $\pm$ 100ppm -40 to +85°C

#### Input Voltage

Code Specification  
 A 3.3V  
 5V

SJ-A1420 Series Continued

Max Reflow Profile

